

application. The substitute specification has been reformatted to include paragraph and claim numbers, so as to conform with new USPTO procedures regarding amendments that were effective march 1, 2001. Additionally, Applicant present new claims 1-48 to prosecute in this divisional application, which replace original claims 1-8 of the parent application. An early indication of allowability regarding claims 1-48 is kindly requested.

### Conclusion

Should there be any outstanding matters which need to be resolved in the present application, the Examiner is respectfully requested to contact Matthew J. Lattig (Registration No. 45,274), in the Washington, D.C. area, at the telephone number listed below.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. §§1.16 or 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

By:

Donald J. Daley  
Reg. No. 34,313

DJD/MJL:ll

P. O. Box 747  
Falls Church, VA 22040-0747  
(703) 205-8000

Attached: marked up copy of original specification

J1046 U.S. PTO  
09/954964

09/19/01

## NETWORK PHOTOGRAPH SERVICE SYSTEM

## BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a network photograph service system which provides a customer with a service [related to a photograph] via a network such as the Internet.

Description of the Related Art

10 For providing a service [related to a photograph] to a customer, a network photograph service has been proposed which provides a variety of services such as ~~the~~ order of extra prints, attachment of a photograph image to an electronic mail message, and download of picture image data by installing a variety of equipment ~~such as~~ <sup>such as</sup> a scanner, a printer, and a server computer comprising a large capacity disc (hereinafter called an image server) in a major wholesale lab [order] to enable a customer to save a picture [he/she] recorded in the image server and ~~to~~ access the image server via a network.

20 The advantage of the network photograph service is that a customer can order a print even when the customer is staying at home or in an office. However [in reality], not everything (such as depositing a film or receiving a print) can be carried out on a network. Therefore, it is <sup>normal</sup> ~~usual~~ to provide the service through <sup>other agencies</sup> such as a local camera shop or a minilab [an agency].  
as

*Customer's perspective*

[When this service is] Viewed from the [customer side], the more agencies there are, the more convenient it is. However, it is preferable to have only one wholesale lab which receives orders, from the viewpoint of easier understanding of where to access when placing an order, or easier data management. Therefore, when a network photograph service is provided, it is [considered to be] better if a wholesale lab has concentrated equipment so that as many agencies as possible can be dealt with.

10           However, in the [above case] where all equipment is concentrated in one large scale wholesale lab as described above, it is inevitable that the date of delivery of a print will be delayed, since a delivery path from an agency to the wholesale lab becomes longer<sup>V</sup>, and a wait time after depositing a film at an agency and before collection of the film is necessary.

15           Even though more rapid processing can be carried out by increasing the number of the wholesale labs to shorten the delivery path while increasing the frequency of collection and delivery, the advantage of a network photograph service system [such as easier understanding of where to access and collective data management] is lost. Moreover, the increased frequency of collection and delivery leads to a rise in collection and delivery cost. Therefore, this idea is not a preferable solution.

#### SUMMARY OF THE INVENTION

25           Based on [consideration of] the above problems, an object of the present invention is to provide a network photograph service

system which can provide a prompt service to a customer without losing the advantages of [a network photograph service system such as] easier understanding, where to access<sup>it</sup> and [collective] data management.

5 A network photograph service system of the present invention comprises at least one laboratory server which has a communication ability via a network and is installed in a laboratory having a picture printer. <sup>The system further comprises</sup> [and] a center server installed in a service center <sup>photo-finishing</sup> <sup>to</sup> [which] receives a printing service order via the network. <sup>photo-finishing</sup> [wherein] 10 The center server carries out processing comprising the steps of storing a picture recorded by a customer of each laboratory as digital image data, making the digital image data accessible on the network, <sup>out of a plurality of photo-finishing laboratories</sup> selecting one laboratory to output a print <sup>photo-finishing</sup> [among the laboratories] in response to order information transferred from the customer via the network, and providing a printing service requested by the order to the customer by transmitting instructing information to the laboratory server installed in the selected <sup>photo-finishing</sup> laboratory.

20 <sup>photo-finishing</sup> XThe "laboratory server" herein referred to means a server computer installed in an individual <sup>photo-finishing</sup> laboratory such as an over-the-counter minilab. <sup>photo-finishing</sup> The "center server" is a server computer installed in a service center which collectively manages image data. Both the laboratory and the center servers have a data recording medium such as a hard disc with a capacity sufficient to store necessary image data. The laboratory server 25

*The role*  
plays ~~a [roll]~~ of a so-called printer server, and ~~has a connection~~ *connects* to a picture printer (in the case where a plurality of picture printers exist, the connection to the printers can be switched from one to another).

5       *The phrase* "Receives a printing service order via a network" means that an order is transferred from a customer as the order information in a predetermined data format. More specifically, the format of the order information is, for example, disclosed on a web <sup>site</sup> ~~site~~ on the Internet, and A customer sends to the center server, via an electronic mail message, the order information created in accordance with the format. Alternatively, if a customer creates an order by inputting information <sup>on</sup> ~~in~~ a predetermined screen, the order may be converted automatically into the predetermined format of the order information and transmitted to the center server.

10      *The picture image obtained by a laboratory* means a picture image obtained ~~by a film scanner~~ by scanning a film that a customer of the laboratory brought in for first printing. Alternatively, a picture image obtained from a memory or the like of a digital camera <sup>which is</sup> ~~brought in by a customer, by using~~ <sup>and which uses</sup> a variety of data reading transferring means such as a card reader, may be included as the picture image. These picture images are hereinafter ~~dealt with~~ <sup>referred to</sup> as digital image data.

15      The reading processing may be carried out at a service center <sup>photofinishing</sup> (in a collective manner). However, if each laboratory carries out this processing, the date of delivery can be made sooner

because collection, ~~and~~ delivery and wait time [~~therefor~~] are not necessary. In this case, [~~an operation for~~] transferring [E] the digital image data obtained by the laboratory to the center server [~~will be necessary~~]. This data transfer [~~to the center server~~] may be carried out via the network each time the laboratory obtains digital image data, or collectively at a predetermined ~~time~~ <sup>time</sup> ~~timing~~. Alternatively, the center server may periodically take in the data from each laboratory server. In some cases (where the data are large), the data may be stored in a medium and then transferred without using a network.

5           The "network" [~~herein referred to~~] means a network as represented by the Internet. The network is meant to include all communication means having a communication speed sufficient to transfer the order information and image data, such as a dedicated line, a CATV network, a dial-up connection, ~~and~~ <sup>or</sup> a LAN.

10           The center server [~~carries out a processing~~ <sup>performs a process which</sup> comprising <sup>es</sup> the steps of storing a picture recorded by a customer of each laboratory as digital image data <sup>and</sup>, making the digital image data accessible on the network <sup>so that the digital image data</sup> [~~is~~] <sup>IS</sup> collectively managed and the customer can refer to the digital image data. When an extra print of a picture is ordered, the picture to be printed is often selected by referring to all pictures recorded. The above image accessing function of the center server [~~is a function~~ <sup>operates</sup>] to carry out this selection on a display screen.

brevet no. 1

*purposes* *photo-finishing* *output* *plurality of laboratories*

"Selecting one laboratory" to output a print [among the laboratories] in response to order information" means to select a laboratory having special equipment, as *the* print outputting laboratory, when the printing service requested by the order needs special equipment to provide the service, such as *generation* *request to* a picture postcard or a creative calendar. Alternatively, [upon receiving order of a print] by letting a customer specify the laboratory at which he/she receives a print, and by including information showing the specified laboratory in the order information, the specified laboratory may be selected as the laboratory to output the print. "Selecting one laboratory" means to include the case where only one laboratory exists, *such that* the sole laboratory is selected [as *the* laboratory] to output a print.

*photo-finishing* *processing* *steps* *providing* *printing* *service* *customer*

"The processing comprising the steps of providing a printing service to the customer" means all processing necessary for providing a printing service to the customer. For example, when an extra print of a picture is ordered from a laboratory, digital image data of the picture needs to be transferred from another laboratory [to *the* laboratory], since the extra print cannot be generated without digital image data of the picture. In other words, "the processing comprising the steps of providing a printing service to the customer" means not only outputting a print by a printer, but also a series of processing steps including such a data transfer.

5           The "order information" specifically means, for example, the processing number specifying what has been ordered (such as an extra print or a postcard generation), the image number identifying a picture, the size of the print, and the number of  
10          the print. The "instruction information" includes not only the order information but also information showing where digital image data can be obtained from (where the digital image data ~~are~~<sup>is</sup> stored) or the like. ~~In this case~~, when the laboratory server which received the instruction information does not have the necessary image data, the server requests the center server or the image server of the laboratory specified as the server from which the image data are obtained transfer the digital image data. Alternatively, the image data necessary for printing may be included in the instruction information.

15          It is preferable for each laboratory server to store a picture recorded by a customer of the laboratory wherein the server is installed as high resolution image data. In this manner, it becomes unnecessary to obtain digital image data from another laboratory when an extra print is ordered by a customer of the  
20          laboratory.

25          When each laboratory server stores digital image data of its customer as described above, digital image data which have been stored in the center server and become accessible may be low resolution image data with a lower amount of data than that of the high resolution image data having been stored in the laboratory

server. In other words, digital image data may be classified in such a manner that the digital image data of the laboratory server are used for outputting a print, while the digital image data in the center server are used for an access via the network.

5 When high resolution image data for outputting a print [are] stored in a laboratory server, it is more effective if the laboratory server carries out the printing, since the amount of data to be transferred [becomes less in that case]. Therefore, when the center server stores digital image data for [an] access, it is preferable that the digital image data [is] stored in correlation 10 with storage location information showing the laboratory server which has high resolution image data of the digital image, so that when the laboratory server to output a print is selected, the [laboratory wherein the] laboratory server storing the high 15 resolution image data of the digital image whose printing has been ordered is selected based on the storage location information.

When a print is output from a laboratory different from the laboratory storing the digital image data, the charge for the printing service rises by a communication charge necessary to transfer the data. When such a data transfer occurs, the service charge paid by the customer should be shared by the laboratory which has output the print <sup>as well as</sup> and the laboratory which is storing the digital image data, since <sup>both</sup> [these] laboratories contribute to providing the printing service. As described above, in the 20 network photograph system of the present invention, the cost 25

varies depending on the content of the instruction information transmitted by the center server, especially on whether or not a data transfer is necessary, or on the amount of data to be transferred. Therefore, the center server may manage transactions which occur between ~~the~~ laboratories or between ~~the~~ 5 laboratory and the service center by recording processing ~~instructions sent~~ <sup>the</sup> instructed to each laboratory server via a transmission of instruction information. ~~Thus, it can be used~~ [the record is used for customer charge control or for <sup>use in</sup> an electronic settlement.] ~~For example.~~

10 "The "printing service" [in this specification] means not only services such as outputting an extra print or generation of a picture postcard as described above, but also all accompanying services carried out before the picture print reaches a customer. <sup>This includes</sup> More specifically, the mailing or delivery service instead of a 15 reception of a finished print over a counter, the service to inform a customer via electronic mail that a print is ready or that a storage period of digital image data in a laboratory is about to expire, the service to extend the storage period by receiving electronic mail from a customer, the service that a customer can 20 select the <sup>finishing</sup> laboratory at which to receive a print, the service that ordered pictures are arranged in an album, and the service that a print is mounted on a photograph mount in the case of a memorial picture. [are all considered as the printing service, for example.]

Therefore, "the instruction information" and "the order information" are meant to include all information necessary for the accompanying service, such as how a print is received and the address or the electronic mail address of the recipient. Such information can [obviously] be used not only for reference, but also for a variety of processing. In other words, with a printer for generating a mailing label connected to the laboratory server, processing such as an automatic mailing label print can be carried out by referring to the name and address of a recipient included in the instruction information, when "the instruction information" specifies mailing of a print.

In a service for generating a manipulated print such as a composite picture, a method using a template has been known. When such a service is provided, the center server may store a template enabling the template to be accessed on the network so that a customer can order a manipulated print using the template. When a manipulated printing service is requested by the order information, information regarding the template specified by the order information may be transferred to the laboratory server as a portion of the instruction information.

*The phrase*  
"Information regarding the template" herein referred to means either the template itself or information showing a suffix of the template or where the template is stored.

However, like the case of the image data above, it is preferable if the amount of data to be transferred is less.

Therefore, it is preferable that each laboratory stores high resolution template for outputting a print, and the information regarding the template has a comparatively small data size, such as the size of only a template ID.

5 When each laboratory server stores high resolution [data of] template, the center server may store the template in the form of low resolution data which have a lower data size than the size of the high resolution data stored in the laboratory server.

10 The template in this specification is meant to include not only data but also a processing procedure such as a macro. More specifically, the template may be a background image comprising a blank space for positioning an image therein, or a [set of such] background image and a procedure "to insert the specified picture in a blank of the background image", for example. Alternatively, ~~the template~~  
15 ~~may comprise~~ procedures such as "to rotate the specified picture by 90°".

X or "to lower the saturation of the specified picture". ~~may be the template, and the case where an image is rotated by 90° by applying the template on the image is possible].~~

20 The network photograph service system of the present invention makes possible communication via <sup>A</sup> the network between the service center to receive an order of a printing service, and the laboratories scattered in each area, and the center server ~~at the service center~~ selects the laboratory to output the ordered print in response to the order information transferred from a

customer via the network, and assigns printing processing to each laboratory instead of carrying out the printing processing by [the center server] itself. Therefore, [the number of] collection of delivery of films or prints is reduced and a prompt service is provided to a customer. In this case, an order reception is carried out collectively by the service center, <sup>to provide</sup> ~~and the advantages such as an~~ ~~of the network photograph service system such as ease of~~ ~~easy understanding where to access and collective data management~~ ~~not lost]~~.

If each laboratory server stores a picture recorded by a customer of the laboratory, wherein the laboratory server is installed <sup>as</sup> [in the form of] high resolution image data, no data transfer occurs when each laboratory is ordered to [carry out the] printing [of] the picture of the customer. A reduction in network load or in communication cost can thus be achieved in this manner.

Thus  
[In this case], the digital image data stored in each laboratory only <sup>has</sup> [have] to be transferred [for printing] <sup>when</sup> <sup>for</sup> necessity. Therefore, the digital image data stored in the center server may be low resolution image data whose resolution has been lowered to such a degree that no problem occurs in displaying the low resolution image data on a display screen when the image data are accessed. In this manner, disc space of the center server can be <sup>conserved</sup> ~~saved~~.

When the laboratory to output a print is selected, if the laboratory storing high resolution image data of the digital image

whose print has been ordered is selected [~~in principle~~], the network load or cost can be reduced<sup>as</sup> compared with the case where another laboratory is selected. This is because large size data transfer is not necessary.

5 When a manipulated printing service using the template is provided as the printing service, if an order is received by disclosing the template as well as the digital image data of a customer on the center server and transmitting information identifying the template used for the processing to the laboratory 10 server, a simple composite picture can be generated in the laboratory, and a prompt printing processing service can be provided.

15 On this occasion, if high resolution template data (~~are~~)  
<sup>plus finishing</sup> stored in the laboratory as ~~are~~<sup>is</sup> the digital image data of the customer, it becomes unnecessary to transfer a template when the center server orders the laboratory server to carry out a manipulated printing service. In this manner, a reduction in network load or communication cost can be achieved.

20 Furthermore, if the template stored in the center server are low resolution data for display, disc space of the center server is saved.

25 Moreover, the cost varies depending on whether or not data should be transferred or on the amount of data to be transferred. Therefore, if the center server carries out transaction management between ~~the~~<sup>2</sup> laboratories or between ~~each~~ laboratory and the center

server based on the instruction information, a service charge control, an electronic settlement and the like becomes easier.

The network photograph service system becomes worthier if more laboratories taking part in the system exist over a wider area. Therefore, to make such a system truly worth while, an effort should be paid to increasing the number of affiliated laboratories by fully considering not only the convenience for a customer and effectiveness of the system, but also laboratory profits. In the form of a system where equipment is concentrated in a service center, over-the-counter laboratories become mere agencies and their profits decrease. Therefore, there is no reason for positively recommending a customer to use the network photograph service. On the other hand, in the present system, over-the-counter laboratories can gain a profit by providing a printing service. Furthermore, in the form where each laboratory stores its customers' high resolution image data, a job related to the data is assigned to the laboratory with priority over other laboratories. Therefore, the more its customers use the network photograph service, the more the laboratory profits.

In other words, the present invention can not only solve the technical problems, but also overcome administrative problems which hinder spreading of a network photograph service system.

[Therefore, the advantage of the present system is extremely great.]

→ → Drawings intro paragraph - here

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagram showing an embodiment of the network photograph service system of the present invention,

5           Figure 2 shows an example of order information,

Figure 3 shows another example of the order information,

Figure 4 is a flow-chart showing an example of laboratory assignment processing by a center server,

Figure 5 is a diagram showing a flow of data in a manipulated printing service,

10           Figure 6 is a diagram showing a configuration of a system for the manipulated printing service,

Figure 7 is a diagram showing an example of how the network photograph service system of the present invention is used, and

15           Figure 8 is a diagram showing an example of how a network photograph service system in which equipment is concentrated in one laboratory is used.

#### DESCRIPTION OF THE PREFERRED EMBODIMENT

Hereinafter, a network photograph service system of the present invention will be explained referring to the accompanying drawings. The form of a system in which equipment is concentrated in one wholesale lab, and its problems, will be explained first referring to Figure 8.

In the system shown in Figure 8, a customer 1 asks for first prints from an agency 13 (121). The first prints may be generated 20 by the agency 13 itself or by a wholesale lab 14 following a request

from the agency 13. In each case, a film (122) from the customer  
1 is temporarily handed to the wholesale lab 14 (122). The  
wholesale lab 14 reads the film using a scanner 7 or the like,  
and stores pictures recorded on the film in an image server 15  
5 as digital image data. If first prints have been ordered from  
the wholesale lab, the prints are generated by a printer 9 or the  
like, and delivered to the agency 13 (123), and then handed to  
the customer 1 via the agency 13 (124).

After the image server 15 has stored digital image data,  
10 the customer 1 can access the image server 15 via the Internet  
5 (125), and order an extra print or the like looking at the stored  
picture image data on a display screen. In response to this order,  
the image server 15 generates a print using the printer 9 or the  
like, and hands the print to the customer 1 (127) by mail or via  
15 the agency (126).

As is obvious from the flow described above, the wholesale  
lab 14 should collect all films from customers of all agencies  
in this system. Therefore, it is possible that delivery of a  
print will be delayed due to a collection and/or delivery queue  
20 or a processing queue. Since the collection and delivery of the  
films and prints are carried out by hand, the date of delivery  
of the finished print may be delayed a couple of days due to the  
collection and/or delivery queue, depending on the number of  
collections and deliveries per day. In other words, in this  
25 system, it becomes easier to order an extra print or the like,

but prompt service is not necessarily guaranteed. Furthermore, if an agency carries out first printing, input processing needs to be carried out by both the agency and the wholesale lab, for example. Therefore, this system often causes inconvenience.

5 In the network photograph service system of the present invention, as shown in Figure 1, a customer 1, a service center 2 which receives an order, and a minilab 3 or a special laboratory 4 with special equipment can all communicate via a network. On this occasion, since the service center<sup>3</sup> and the special laboratory<sup>4</sup> need to communicate ~~especially~~ frequently, they use high speed 10 lines so that they can handle more orders promptly.

In the embodiment shown in Figure 1, digital image data input is carried out by the minilab 3. When the customer orders first prints to the minilab 3, the minilab 3 reads a film using a scanner 15 7 and generates first prints using a printer 9. The digital image data read by the scanner 7 are stored in a laboratory server 8 after the generation of the first prints. On this occasion, low resolution image data which ~~are~~<sup>is</sup> the digital image data in a reduced resolution (hereinafter called a thumbnail image) are generated 20 and transferred to a center server 12 in the service center 2. The laboratory server 8 stores not only the digital image data of the customer but also a template thereof.

The center server 12 in the service center 2 stores the thumbnail image transferred from each laboratory in correlation 25 with the laboratory from which the image has been sent, while

making the thumbnail image accessible on the network. On this occasion, the thumbnail image does not need a particularly high quality, since the customer uses the thumbnail image only to confirm the picture upon an order. In order to save disc space,  
5 it is more preferable if the thumbnail image has a smaller amount of data. In this embodiment, digital image data that the laboratory server 8 stores for outputting a print has 4 base pixels (approximately 1024 × 1792 pixels) which are necessary for  
10 outputting an L size print at 300 dpi, while the digital image data that the center server 12 stores for an access via the network has 1/4 base pixels (approximately 368 × 256 pixels). The center server 12 also stores a thumbnail of the template that the laboratory server 8 stores so that the customer can access the template via the network.

15 When the digital image data ~~are~~ made accessible, the customer only has to confirm ~~his/her~~ <sup>their</sup> own pictures. In other words, ~~he/she does~~ <sup>they do</sup> not want others to see ~~his/her~~ <sup>their</sup> pictures. Therefore, by ~~an authentication~~ using a password, each customer has only a limited access to data he/she can see. The password is determined  
20 by a customer when he/she orders first prints. Alternatively, the minilab determines the password by assigning an appropriate one.

As for the access to the center server, the above service is provided in the form of a web page if on the Internet, and the

customer can access the center server using a browser such as Netscape Navigator. Alternatively, if the service is provided as another original communication service, dedicated software may be distributed to each customer. In each case, the customer 1  
5 can request a printing service without going to the minilab 3 by carrying out a predetermined input on an order screen through confirmation of the thumbnail image of ~~his/her~~<sup>their</sup> picture stored in the center server or selection of a template via the network from ~~his/her~~<sup>their</sup> house or office, or through generation of order 10 information in a predetermined format and transmission of the information via electronic mail.

On this occasion, the order information transmitted from the customer to the center server 12 is like the example shown 15 in Figure 2. The order information contains information necessary for extra prints, such as the image number, the size, the number of extra prints, and how the finished prints are received. Furthermore, in an order of a manipulated print, the template number or the like is also included in the order information. Moreover, the content of the service which can be 20 provided through the network includes not only the service accompanying the print output, but also all services related to the printing service. For example, when a storage period of digital image data in the laboratory 8 will expire in a few days but the customer has not decided the picture to order for an extra

print, a request for an extended storage in this case can be considered as a part of the services related to printing.

A variety of data structures of the order information are also possible. For example, Microsoft Corp. has proposed<sup>1</sup> a structured storage technique by which several kinds of data [~~of different nature~~] are stored in a file in a hierarchy. The order information can be generated as an order file shown in Figure 3 by using this technique.

The format of the order information may be defined depending on the service to be provided, and the format shown in Figures 2 and 3 are mere examples.

When the center server 12 receives such order information, it assigns the laboratory for outputting the ordered print. For instance, Figure 4 shows an example of the processing to assign the laboratory for outputting the ordered print in the case where the order information in Figure 2 is used. In this example, it is judged whether or not the requested processing needs special equipment by referring to the data showing the processing number. If the processing requires the special equipment, the special laboratory 4 is selected as the laboratory to output the print, and instruction information in a predetermined format is generated and transferred to the laboratory server 8 in the special laboratory 4. On this occasion, the special laboratory 4 does not have digital image data to be printed. Therefore, the

instruction information includes the information showing the laboratory which ~~has~~<sup>does have</sup> the digital image data.

When processing [which does not need the special equipment, such as] an ordinary extra print, is requested, it is checked if whether the customer wants to receive the print over the counter, or by mail or delivery, by referring to order information data showing how the print is received. In the case of mailing or delivery, it is no more convenient to the customer [no matter] which laboratory outputs the print he/she has ordered. Therefore, the laboratory which is most effective for the system, that is, the laboratory which stores the high resolution image data for outputting the ordered print is selected.

When the customer wants to receive the print over the counter, the order information data showing the laboratory at which the print is received is referred to, and the laboratory is selected as the laboratory to output the print. When no laboratory is specified in the order information, the laboratory which stores the high resolution image data is selected. When the laboratory specified by the customer does not have the high resolution image data, the information showing where the high resolution image data is stored is included in the order information, as is the case where the special laboratory 4 is selected.

When the center server 12 transmits the order information to the laboratory selected as described above, it records the content of the order and calculates a data storage fee, a

communication charge and the like to be paid to each laboratory by periodically summing up the amount of data transferred. In this manner, transactions between the center server 12 and each laboratory, or between the laboratories, are managed. This management is carried out in this manner, because each laboratory can gain an appropriate profit by printing or by storing digital image data of its customers. Such data are obviously used in a charge billing system to customers as well.

The laboratory server 8 which received the order information carries out the processing such as outputting an extra print according to the content of the order included in the order information, and hands the print to the customer or arranges mailing or the like. On this occasion, the hand-over to the customer or a mailing arrangement should be carried out by hand, as has been carried out conventionally. However, the laboratory server 8 can carry out processing to help such operations, for example, to print a mailing label automatically by referring to the order information data showing the recipient, and to notify the recipient of the print output finish by automatically sending him/her an electronic mail.

An example of such a service viewed from the flow of data is shown in Figure 5. Regarding the manipulated printing service using the template, data ~~in~~ managed by a personal computer 6 of the customer, the center server 12, and the laboratory server 8, in addition to the flow of the data, are shown in Figure 5.

As described above, the laboratory server 8 stores high resolution image data 21 of the customer's picture and high resolution template 23 thereof. The center server 12 stores a low resolution template 24 which corresponds to the high resolution template 23, because whenever a new template is generated in the laboratory, a low resolution template corresponding to the new template is also registered in the center server. Meanwhile, low resolution image data 22 corresponding to the high resolution image data 21 are also registered in the center server upon a request from the customer.

The customer refers to (and downloads upon necessity) the low resolution image data 22 and the low resolution template 24 disclosed on the center server 12 and composes them using the personal computer 6. However, the processing carried out at this stage, such as composition, aims to generate the order information, and the processed image obtained through the processing is used for confirmation only. The procedure of the processing carried out by the customer is recorded by the function of dedicated software installed in the personal computer 6. The procedure is taken in as a portion of the order information 20 when the order information is generated. The order information 20 also includes information showing an image 22a and a template 24a specified and used by the customer.

The order information 20 is received by the center server 12, and the center server 12 transmits instruction information

25 to the laboratory selected by referring to the order information  
20. At this time, the instruction information 25 includes the  
information showing the image 22a, the template 24a, and the  
processing procedure. The laboratory server 8, which receives  
5 the instruction information including such information, searches  
the hard disc for the high resolution template 23a corresponding  
to the template 24a and high resolution image data 21a  
corresponding to the image 22a, based on the information, and  
outputs the print after the processing following the processing  
10 procedure.

Such a service as described above can be implemented by the  
system configuration shown in Figure 6, for example.

The personal computer 6 of the customer who carries out the  
order generation processing will be explained first. A WWW  
15 browser 30 has been installed in the personal computer 6. The  
program which carries out the order generation processing is  
provided as a plug-in of the browser. Alternatively, the function  
which carries out only a portion of the order generation processing  
is provided as the plug-in, and the other functions may be  
20 installed as application software independent from the browser.

The example in Figure 6 shows the case where functions for  
browsing and downloading the low resolution image data and  
template, as well as a function for uploading an order file are  
provided as the plug-in, while a processing application 31 for  
25 processing the image data and template which have been downloaded,

and an order file generating module 32, are provided as application software.

In this example, in the processing application 31, if the size and the number of a print are specified as in the case of ordinary printing (the printing by a printer connected to a personal computer), an order file is automatically generated by the function of the order file generating module 32.

If the low resolution image data and template are provided by a medium 11, the WWW browser 30 is used for browsing the data stored in the medium 11 and also for copying data from the medium 11 to the hard disc of the personal computer 6.

The configuration of the center server 12 will be explained next. As described above, the center server 12 is a server computer comprising a large capacity hard disc and a variety of communication equipment. The server computer 12 is used for providing the order receiving service in the form of a web page.

A WWW application server 36 which communicates with the WWW browser 30 of the personal computer 6 accesses low resolution image data base 33 and low resolution template data base 34 in response to the customer's request, and obtains necessary data, then transfers the data to the personal computer 6. The access to the data bases 33 and 34 may be carried out by an original protocol. However, by using a protocol 35 which is used by each company in common, it becomes possible to use a data base in another company's system in the same manner as the data base in the center server

of its own company. In other words, it is preferable that the access to the data base or the like is carried out by defining the common image accessing protocol 35 for a search, a transfer, and access right management of the templates and images.

5           The WWW application server 36 receives the order file 20 uploaded by the user, selects the laboratory server 8 which is best-suited for processing the order, and transfers the order file 20 as it is or after adding necessary instruction information thereto. In other words, an order file transmitting receiving  
10          protocol 37 in Figure 6 is the protocol for assigning the laboratory for printing, in response to the order content. It is also preferable to use a common order file transmitting receiving protocol.

15          A program 42 which analyzes the order file 20 transferred from the center server 12 and a program 41 which carries out the processing and printing based on the instruction in the order file 20 are installed in the laboratory server 8. After analyzing the order file 20, if the access right to the image specified in the order file is denied (if the password necessary for the access is not included in the order file), no processing and printing are carried out. If the access right is confirmed, the above program obtains necessary data from high resolution image data base 40 and high resolution template data base 38, and outputs the manipulated print.  
20

The configuration and the function of the network photograph service system of the present invention has been described above. Next, an example of how convenient the system is to use will be described with reference to Figure 7.

5       For example, assume the case where a customer records pictures with his/her friend who came from overseas, and first prints are then ordered from a minilab 3a nearby (101). The first prints are immediately processed by the minilab 3a, and the film is returned to the customer when the prints are finished (102).

10      Assume that the customer records other pictures with the same friend at the friend's house overseas. Conventionally, first prints of pictures recorded on a trip have been ordered after the trip. However, since every operation, except for printing a film, can be carried out via the network in the network photograph service system of the present invention, it is highly likely that

15      this system has affiliated<sup>print finishing</sup> laboratories overseas. Therefore, even when first prints are ordered from a minilab 3b near the friend's house (103), and the prints are received there (104), an extra print can be ordered after the customer returns to his/her

20      country.

After the customer returns, he/she accesses the center server 12 from the personal computer 6 at home and orders extra prints of these pictures (105). At this time, for example, among the pictures whose first prints were ordered from the minilab 3a,

25      an extra print of a picture a is ordered for the customer while

a picture b is for the friend, and among the pictures whose first prints were ordered from the minilab 3b, an extra print of a picture c is ordered for the customer.


As for the pictures for the customer, the minilab 3a is specified as the laboratory at which the prints are received. As for the picture for the friend, mailing may be specified as the method to receive the print. However, in the case of air mail, it takes more than one day for the print to reach the friend. On the other hand, if an order is carried out with the friend being specified as the recipient and the laboratory 3b as the laboratory at which the print is received, the print can reach the friend on the day of the order at the earliest.

When such an order is carried out, the center server 12 instructs the image server in the minilab 3a to output the prints of the pictures a and c, while notifying the image server of the network address of the laboratory server in the minilab 3b which stores the picture c (106). In this manner, the laboratory server in the minilab 3a can obtain the digital image data of the picture c by a transfer of the data from the laboratory server in the minilab 3b (107). Likewise, the center server 12 instructs the printing of the picture b to the minilab <sup>3a</sup>~~3b~~ and notifies the laboratory 3b of the network address of the laboratory server in the minilab 3a which stores the picture b (108). In this manner, the laboratory server in the minilab 3b can obtain the digital image data of the picture b by a transfer of the data from the

laboratory server in the minilab 3a (109). By such transfer processing of the digital image data, the pictures a and c are printed at the minilab 3a and provided to the customer (110), while the picture b is printed at the minilab 3b and provided to the customer's friend (111). In this system if the customer notifies the friend of the customer's password, the friend can order a picture he/she wants directly.

As shown by the above examples, according to the network photograph service system of the present invention, the printing service can be received upon necessity, at a desired place, and in a shorter time than before, regardless of the location of the laboratory where the first prints have been ordered. This is extremely convenient not only for the example shown in Figure 5 but also for business, such as the case where a picture suddenly becomes necessary in a business activity going on from place to place.

In the embodiment described above, the center server 12 stores the thumbnail images for the access via the network while the laboratory server 8 stores the high resolution image data for printing. However, it is needless to say that the center server may store the high resolution image data for printing which are also used as the image for access, while the laboratory server 8 carries out printing only, without storing the high resolution image data.



These and other objects of the present application will become more readily apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples

while indicating preferred embodiment of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention

to come appear & those skilled in the art know this detailed description

*Replaced by  
new claims 1-34  
for 53(b)  
divisional*

What is claimed is;

1. A network photograph service system comprising:  
at least one laboratory server with a communication ability  
via a network and installed in a laboratory having a picture  
5 printer; and

a center server installed in a service center which receives  
a printing service order via the network, wherein the center server  
carries out the processing comprising the steps of storing a  
10 picture recorded by a customer of each laboratory as digital image  
data, making the digital image data accessible on the network,  
selecting one laboratory to output a print among the laboratories  
in response to order information transferred from the customer  
via the network, and providing to the customer the printing service  
requested in the order by transmitting instruction information  
15 to the laboratory server installed in the selected laboratory.

2. A network photograph service system as defined in Claim  
1 wherein each said laboratory server stores the picture image  
obtained by the laboratory in which the laboratory server is  
installed as high resolution image data.

20 3. A network photograph service system as defined in Claim  
2 wherein the digital image data stored in the center server and  
made accessible by the center server are low resolution image data  
with a lower amount of data than the data amount of the high  
resolution image data stored in the laboratory server.

4. A network photograph service system as defined in Claim  
2 or 3 wherein the center server stores the digital image data  
in correlation with storage location information showing the  
laboratory server in which the image data are stored as high  
resolution image data, and selects, upon selection of the  
laboratory to output the image, the laboratory in which the  
laboratory server stores the high resolution image data of the  
picture image whose print has been ordered, based on the storage  
location information.

5  
10  
15  
10. A network photograph service system as defined in any  
one of the Claims 1 to 4 wherein the center server records the  
processing instructed to each laboratory server by transmitting  
the instruction information, and manages a transaction occurring  
between the laboratories and/or between the center server and each  
laboratory, based on the record.

15  
20  
11. A network photograph service system as defined in any  
one of the Claims 1 to 5 wherein the center server stores a template,  
makes the template accessible on the network, and comprises a  
function for transmitting information regarding the template  
specified by the order information as a portion of the instruction  
information when a manipulated printing service using the template  
is requested by the instruction information, and

the laboratory server generates the manipulated print using  
the template, based on the instruction information.

7. A network photograph service system as defined in Claim 6 wherein each said laboratory server stores high resolution data of the template.

8. A network photograph service system as defined in Claim 5 7 wherein the center server stores the template as low resolution image data with a lower amount of data than the data amount of the high resolution image data which are stored in the laboratory server.

ABSTRACT OF THE DISCLOSURE

By [open] providing a network photograph service, a prompt service can be provided to a customer without losing the advantages [thereof such as ease] easier of understanding where to access<sup>t</sup> and collective data management. A service center receiving an order of a printing service and a minilab or a special laboratory spread across a plurality of places are able to communicate through a network. The center server in the service center selects and assigns ~~the~~ <sup>A</sup> laboratory ~~for~~ printing the ordered picture, in response to [an] order information transferred from a customer via the network so that the printing processing can be carried out by ~~the~~ <sup>a photo-finishing</sup> laboratory specified by the customer instead of the center server.

when placing an order.